

At your side.  
**brother**®

HL-1470N

Networking

Network Printing Solutions

HL-1470N



## HL-1470N High Speed Network Laser Printer

up to  
**14**  
ppm

Up to 14ppm



Network Ready



Windows &  
DOS Compatible



Mac OS  
Compatible



PCL®6/BR-Script®2



USB Standard



Optional  
Lower Tray

## networking

The speed of communication required in a modern business environment makes the need for effective networking even more important than ever. The Brother HL-1470N laser printer offers the benefit of network connectivity as just one

of its many standard features. Combine this with an impressive print speed of up to 14 pages per minute, high quality 1200 x 600 dpi resolution and a versatile range of connectivity options, including Apple Mac. Combine all these features and you have the ideal printing solution for the small business workgroup.

The HL-1470N printer is quick and easy to install and includes the benefit of comprehensive state of the art technical support with Windows Interactive Animations providing a user friendly step by step guide to your new printer. Plus, for additional peace of mind, you can enjoy direct access to the Brother Solutions Centre web site.

- Up to 14 pages per minute print speed
- Up to 1200 x 600 dpi resolution
- 8MB standard memory, expandable up to 36MB
- Parallel and USB ports as standard
- 10/100Base TX Ethernet connectivity as standard
- Powerful Network management software
- Wide compatibility  
*Optimised drivers for Windows®95/98/Me/NT®4.0/Windows 2000 Driver for Mac OS 8.51 or later PCL6® emulation BR-Script®2 (Postscript Level 2® Language Emulation), IBM Proprinter XL®, Epson FX-850®*
- Up to 250 sheet universal paper cassette
- Manual paper feed slot
- Optional lower tray for extra 250 sheet input
- Dedicated web support page on [solutions.brother.com](http://solutions.brother.com)
- Easy replacement long-life consumables



Toner &amp; Drum

## MODEL HL-1470N

ENGINE		PAPER HANDLING	
Technology	Electrophotographic	Paper Input <sup>*10</sup>	Paper Cassette (Standard) 250 Sheets Manual Feed 1 Sheet Paper Cassette (Option) 250 Sheets
Print Speed	Up to 14 ppm	Paper Output <sup>*10</sup>	Face Down 150 Sheets Face Up 1 Sheet
First Print Time	Less than 15 sec <sup>*11</sup>	<b>MEDIA SPECIFICATIONS</b>	
Resolution	1200 x 600 dpi for graphics 600 dpi 300 dpi 600 dpi	Media Types	Manual Feed Plain Paper, Bond Paper, Recycled Paper, Envelopes, Labels, and Transparencies Paper Cassette (Standard) Plain Paper, Bond Paper, Recycled Paper, Transparencies <sup>*11</sup> Paper Cassette (Option) Plain Paper, Bond Paper, Recycled Paper
	1200 x 600 dpi for graphics 600 dpi 300 dpi 600 dpi	Media Weights	Manual Feed 60 - 161 gsm Paper Cassette 60 - 105 gsm
	300 dpi 300 dpi	Media Sizes	Manual Feed Custom: 69.8 x 116 - 216 x 356 mm Paper Cassette (Standard) A4, Letter, B5(ISO), B5(JIS), A5, B6(ISO), A6, Exe Paper Cassette (Option) A4, Letter, B5(ISO), B5(JIS), A5, Exe
	300 / 600 dpi	<b>PRINTER DRIVER FUNCTIONS<sup>*12</sup></b>	
<b>CONTROLLER</b>		Page Layout	N in 1 Printing 2, 4, 9, 16, 25 in 1 page Poster Printing 1 in 4, 9, 16, 25 Watermark Printing Yes
Processor	Fujitsu MB86832 66MHz	Others	Quick Print Setup <sup>*13</sup> Manual Duplex
Memory	8MB 1 SIMM slot : expandable up to 36MB	<b>SUPPLIES</b>	
Interface	Standard IEEE 1284 Parallel, USB, 10/100 BaseTX Option IrDA (IR-1000)	Toner	Standard Cartridge TN-6300 up to 3,000 A4 pages @5% coverage High Yield Cartridge TN-6600 up to 6,000 A4 pages @5% coverage
Network Connectivity	10/100 BaseTX (Auto Negotiation) - Standard TCP/IP, AppleTalk, IPX/SPX, DLC/LC BRAdmin Professional <sup>*3</sup> Web Based Management <sup>*4</sup>	Drum	DR-6000 up to 20,000 A4 pages (1 page / job)
Emulation	PCL6, PostScript Level II language emulation, Epson FX-850, IBM Proprinter XL 66 scalable fonts, 12 bitmap fonts, 11 bar codes <sup>*5</sup> 66 fonts	<b>DIMENSIONS / WEIGHTS</b>	
Resident Fonts	PCL PS2 language emulation	Dimensions	360 x 370 x 345 mm (WxDxH)
<b>SOFTWARE</b>		Weights	Approx. 9.3 kg including the drum unit and toner cartridge
Printer Driver	PCL Driver for Windows 95 / 98 / Me, NT4.0 / 2000, and Mac OS 8.5 - 9.1/OSX PostScript Printer Description (PPD) file for Windows 95/98/Me/NT4.0, Windows 2000 and Mac OS 8.51 - 9.1/OSX <sup>*6</sup>	<b>OTHERS</b>	
Utilities	Automatic E-mail Printing <sup>*7</sup> Interactive Help <sup>*8</sup> Status Monitor Driver Deployment Wizard <sup>*9</sup>	Power Consumption	Printing (Average) 340 W, or less Standby 70 W, or less Sleep 12 W, or less Printing 50 dB (A), or less Standby Silent Power Saving Yes Toner Saving Yes
<b>CONTROL PANEL</b>		Noise Level	
Display	4 LEDs	Ecology	
Switch	1 Key		

\*1 From standard paper cassette when loading A4 size

\*2 High Resolution Control

\*3 Brother original Windows utility for printer and print server management

\*4 Printer and print server management through Web browser

\*5 Code39, Interleaved 2 of 5, EAN-8, EAN-13, UPC-A, UPC-E, EAN-128, Codabar, FIM(US-PostNet), ISBN, Code128\*

\*6 EtherTalk only

\*7 Utility software that automatically prints e-mail messages (For Windows 95/98/Me)

\*8 Instructional movies

\*9 The Driver Deployment Wizard guides you through the steps of installing a Brother printer on a locally connected or networked Windows PC

\*10 Calculated with 80gsm paper

\*11 Up to 10 sheets

\*12 Some functions are not available on PS2 and Mac Drivers

\*13 A function that enables you to change the printer driver settings without opening the Property dialogue