HP Designjet T1200 HD Multifunction Printer



Do and offer more - process, print, scan, and copy



Rely on one complete, easy, integrated solution

- You can depend on this convenient single-vendor solution—built together to work together.
- Experience easy operation of scan, copy, and print functions.
- Save valuable workspace with this single, integrated multifunction solution.

Take your productivity to the next level

- Save time and paper with 2 online rolls.
- You're back to business in no time with an HP MFP that scans, copies, and prints your projects quickly.
- Batch scanning and printing is fast and easy thanks to free HP Instant Printing and collating features.

See top quality results from any original

- Get a high level of quality—from line drawings to maps to posters—with 4 camera CCD scanning technology.
- Experience added versatility when you scan, print AEC, CAD, and GIS documents.
- Produce fine lines, crisp text, and vivid color with Original HP inks, including 2 blacks and a gray ink.
- Transform your everyday printing using HP everyday bond papers with ColorPRO Technology.



Eco Highlights

- Save paper with two roll configuration, print image nesting, blank print area detection, image auto rotate, and realistic print previews
- Less ink wasted thanks to efficient installation and maintenance routines
- Free, convenient cartridge and printhead recycling¹

Please recycle large-format printing hardware and printing supplies. Find out how at our website: **hp.com/ecosolutions**

Program availability varies. Please check <u>hp.com/recycle</u> for details.

Technical specifications

Line drawings1	
Line drawings ¹	Fast: 28 sec/page on A1/D, 103 A1/D prints per hour
Color images ²	Fast: 41 m²/hr (445 ft²/hr) on coated media
	Best: 3.1 m ² /hr (33.3 ft ² /hr) on glossy media
Print resolution	Up to 2400 x 1200 optimized dpi
	Roll: 5 x 5 x 5 x 5 mm (0.2 x 0.2 x 0.2 x 0.2 in) (borderless on
tert x right)	photo papers) Sheet: 5 x 16.75 x 5 x 5 mm (0.2 x 0.67 x 0.2 x 0.2 in)
Technology	HP Thermal Inkiet
	Dye-based (C, M, Y, G, PK); pigment-based (MK)
	6 pl (C, M, PK, G), 9 pl (Y, MK)
Line accuracy	+/- 0.1%3
Minimum line width	0.02 mm (0.0008 in) (HP-GL/2 addressable)
Guaranteed minimum	0.06 mm (0.0024 in) (ISO/IEC 13660:2001(E)) ⁴
line width	
Scan speed ⁵	Color: 5.1 cm/sec (2 in/sec) Black-and-white: 15.2 cm/sec (6 in/sec)
Scan/copy resolution	Up to 9600 dpi (Enhanced mode) with variable resolution settings from 50 dpi in increments of 1 dpi
Max scan width	1067 mm (42 in)
Max scan thickness	15.2 mm (0.6 in)
Reduction/enlargement	1 to 10,000%
Maximum copies	1000 copies
Copier settings	Type of original, image crop and align preview, lightness, saturation and RGB controls, sharpen/blur, mirror copy, enlarge/reduce, paneling, tiling, nesting, accounting, batch
Handling	Printer: sheet feed, two automatic roll feeds, automatic roll-
riariamig	switching, automatic cutter
	Scanner: straight-through scan paper path for sheet and
0.1.1	cardboard originals
	32 GB (virtual) ⁶ , 160 GB hard disk
	1 GB, 160 GB hard disk
Interfaces	Printer: Gigabit Ethernet (1000Base-T), Hi-Speed USB 2.0
(standard)	certified, EIO Jetdirect accessory slot Scanner: Gigabit Ethernet (1000Base-T), Hi-Speed USB 2.0
(standard) Print languages	certified, EIO Jetdirect accessory slot
	certified, EIO Jetdirect accessory slot Scanner: Gigabit Ethernet (1000Base-T), Hi-Speed USB 2.0 certified, FireWire (IEEE-1394a compliant) Adobe* PostScript* 3™, Adobe PDF 1.7, TIFF, JPEG, HP-GL/2,
Print languages	certified, EIO Jetdirect accessory slot Scanner: Gigabit Ethernet (1000Base-T), Hi-Speed USB 2.0 certified, FireWire (IEEE-1394a compliant) Adobe* PostScript* 3™, Adobe PDF 1.7, TIFF, JPEG, HP-GL/2, HP-RTL, CALS G4, HP PCL 3 GUI HP-GL/2, HP-RTL, and PostScript drivers for Windows® (optimized for AutoCAD 2000 and higher); PostScript drivers for Mac OS X and Linux; support for Citrix XenApp and Citrix
Print languages Drivers (included)	certified, EIO Jetdirect accessory slot Scanner: Gigabit Ethernet (1000Base-T), Hi-Speed USB 2.0 certified, FireWire (IEEE-1394a compliant) Adobe* PostScript* 3™, Adobe PDF 1.7, TIFF, JPEG, HP-GL/2, HP-RTL, CALS G4, HP PCL 3 GUI HP-GL/Z, HP-RTL, and PostScript drivers for Windows® (optimized for AutoCAD 2000 and higher); PostScript drivers for Mac 05 X and Linux; support for Citrix XenApp and Citrix XenServer environments
Print languages Drivers (included)	certified, EIO Jetdirect accessory slot Scanner: Gigabit Ethernet (1000Base-T), Hi-Speed USB 2.0 certified, FireWire (IEEE-1394a compliant) Adobe* PostScript* 3**, Adobe PDF 1.7, TIFF, JPEG, HP-GL/Z, HP-RTL, CALS G4, HP PCL 3 GUI HP-GL/Z, HP-RTL, and PostScript drivers for Windows* (optimized for AutoCAD 2000 and higher); PostScript drivers for Mac 0S X and Linux; support for Citrix XenApp and Citrix XenServer environments 1900 x 1000 x 1600 mm (74.8 x 39.4 x 63 in)
Print languages Drivers (included) MFP Shipping	certified, EIO Jetdirect accessory slot Scanner: Gigabit Ethernet (1000Base-T), Hi-Speed USB 2.0 certified, FireWire (IEEE-1394a compliant) Adobe* PostScript* 3**, Adobe PDF 1.7, TIFF, JPEG, HP-GL/2, HP-RTL, CALS G4, HP PCL 3 GUI HP-GL/2, HP-RTL, and PostScript drivers for Windows* (optimized for AutoCAD 2000 and higher); PostScript drivers for Mac OS X and Linux; support for Citrix XenApp and Citrix XenServer environments 1900 x 1000 x 1600 mm (74.8 x 39.4 x 63 in) 1930 x 766 x 1529 mm (75.98 x 30.16 x 60.2 in)
Print languages Drivers (included) MFP Shipping MFP Shipping x HP Designjet T1200 Print quick reference guides, so scanner documentation s	certified, EIO Jetdirect accessory slot Scanner: Gigabit Ethernet (1000Base-T), Hi-Speed USB 2.0 certified, FireWire (IEEE-1394a compliant) Adobe* PostScript* 3**, Adobe PDF 1.7, TIFF, JPEG, HP-GL/2, HP-RTL, CALS G4, HP PCL 3 GUI HP-GL/2, HP-RTL, and PostScript drivers for Windows* (optimized for AutoCAD 2000 and higher); PostScript drivers for Mac OS X and Linux; support for Citrix XenApp and Citrix XenServer environments 1900 x 1000 x 1600 mm (74.8 x 39.4 x 63 in) 1930 x 766 x 1529 mm (75.98 x 30.16 x 60.2 in) 200 kg (440 lb) 280 kg (617 lb) er, printheads, introductory ink cartridges, printer stand, spindle, stup posters, start-up software, scanner, touchscreen (panel PC) oftware, system recovery software, customer service guide, USE
Print languages Drivers (included) MFP Shipping MFP Shipping x HP Designjet T1200 Print quick reference guides, so scanner documentation s cable, FireWire cable, Ethe	certified, EIO Jetdirect accessory slot Scanner: Gigabit Ethernet (1000Base-T), Hi-Speed USB 2.0 certified, FireWire (IEEE-1394a compliant) Adobe* PostScript* 3™, Adobe PDF 1.7, TIFF, JPEG, HP-GL/2, HP-RTL, CALS G4, HP PCL 3 GUI HP-GL/2, HP-RTL, and PostScript drivers for Windows® (optimized for AutoCAD 2000 and higher); PostScript drivers for Mac OS X and Linux; support for Citrix XenApp and Citrix XenServer environments 1900 x 1000 x 1600 mm (74.8 x 39.4 x 63 in) 1930 x 756 x 1529 mm (75.98 x 30.16 x 60.2 in) 200 kg (440 lb) 280 kg (617 lb) er, printheads, introductory ink cartridges, printer stand, spindle, etup posters, start-up software, scanner, touchscreen (panel PC) oftware, system recovery software, customer service guide, USE ernet cable, power cords
Print languages Drivers (included) MFP Shipping MFP Shipping M HP Designjet T1200 Print quick reference guides, so scanner documentation s cable, FireWire cable, Etho Operating temperature	certified, EIO Jetdirect accessory slot Scanner: Gigabit Ethernet (1000Base-T), Hi-Speed USB 2.0 certified, FireWire (IEEE-1394a compliant) Adobe* PostScript* 3™, Adobe PDF 1.7, TiFF, JPEG, HP-GL/Z, HP-RTL, CALS G4, HP PCL 3 GUI HP-GL/Z, HP-RTL, and PostScript drivers for Windows® (optimized for AutoCAD 2000 and higher); PostScript drivers for Mac OS X and Linux; support for Citrix XenApp and Citrix XenServer environments 1900 x 1000 x 1600 mm (74.8 x 39.4 x 63 in) 1930 x 766 x 1529 mm (75.98 x 30.16 x 60.2 in) 200 kg (440 lb) 280 kg (617 lb) er, printheads, introductory ink cartridges, printer stand, spindle, etup posters, start-up software, scanner, touchscreen (panel PC) oftware, system recovery software, customer service guide, USE ernet cable, power cords 5 to 40°C (41 to 104°F)
Print languages Drivers (included) MFP Shipping MFP Shipping MFP Ship	certified, EIO Jetdirect accessory slot Scanner: Gigabit Ethernet (1000Base-T), Hi-Speed USB 2.0 certified, FireWire (IEEE-1394a compliant) Adobe* PostScript* 3™, Adobe PDF 1.7, TIFF, JPEG, HP-GL/2, HP-RTL, CALS G4, HP PCL 3 GUI HP-GL/2, HP-RTL, and PostScript drivers for Windows® (optimized for AutoCAD 2000 and higher); PostScript drivers for Mac OS X and Linux; support for Citrix XenApp and Citrix XenServer environments 1900 x 1000 x 1600 mm (74.8 x 39.4 x 63 in) 1930 x 766 x 1529 mm (75.98 x 30.16 x 60.2 in) 200 kg (440 lb) 280 kg (617 lb) er, printheads, introductory ink cartridges, printer stand, spindle, stup posters, start-up software, scanner, touchscreen (panel PC) oftware, system recovery software, customer service guide, USE ernet cable, power cords 5 to 40°C (41 to 104°F) -25 to 55°C (-13 to 131°F)
Print languages Drivers (included) MFP Shipping MFP Shipping MFP Ship	certified, EIO Jetdirect accessory slot Scanner: Gigabit Ethernet (1000Base-T), Hi-Speed USB 2.0 certified, FireWire (IEEE-1394a compliant) Adobe* PostScript* 3™, Adobe PDF 1.7, TIFF, JPEG, HP-GL/2, HP-RTL, CALS G4, HP PCL 3 GUI HP-GL/2, HP-RTL, and PostScript drivers for Windows® (optimized for AutoCAD 2000 and higher); PostScript drivers for Mac 0S X and Linux; support for Citrix XenApp and Citrix XenServer environments 1900 x 1000 x 1600 mm (74.8 x 39.4 x 63 in) 1930 x 766 x 1529 mm (75.98 x 30.16 x 60.2 in) 200 kg (440 lb) 280 kg (617 lb) er, printheads, introductory ink cartridges, printer stand, spindle, etup posters, start-up software, scanner, touchscreen (panel PC) oftware, system recovery software, customer service guide, USE ernet cable, power cords 5 to 40°C (41 to 104°F) -25 to 55°C (-13 to 131°F) 20 to 80% RH
Print languages Drivers (included) MFP Shipping MFP Shipping X HP Designjet T1200 Print quick reference guides, st scanner documentation scable, FireWire cable, Eth Operating temperature Storage temperature Operating humidity Sound pressure	certified, EIO Jetdirect accessory slot Scanner: Gigabit Ethernet (1000Base-T), Hi-Speed USB 2.0 certified, FireWire (IEEE-1394a compliant) Adobe* PostScript* 3™, Adobe PDF 1.7, TIFF, JPEG, HP-GL/Z, HP-RTL, CALS G4, HP PCL 3 GUI HP-GL/Z, HP-RTL, and PostScript drivers for Windows® (optimized for AutoCAD 2000 and higher); PostScript drivers for Mac 0S X and Linux; support for Citrix XenApp and Citrix XenServer environments 1900 x 1000 x 1600 mm (74.8 x 39.4 x 63 in) 1930 x 766 x 1529 mm (75.98 x 30.16 x 60.2 in) 200 kg (440 lb) 280 kg (617 lb) er, printheads, introductory ink cartridges, printer stand, spindle, etup posters, start-up software, scanner, touchscreen (panel PC) oftware, system recovery software, customer service guide, USI ernet cable, power cords 5 to 40°C (41 to 104°F) -25 to 55°C (-13 to 131°F) 20 to 80% RH 47 dB(A) (active); 32 dB(A) (standby)
Print languages Drivers (included) MFP Shipping MFP Shipping X HP Designjet T1200 Print quick reference guides, so scanner documentation scable, FireWire cable, Ethe Operating temperature Storage temperature Operating humidity Sound pressure Sound power 120 watts (printing); 300	certified, EIO Jetdirect accessory slot Scanner: Gigabit Ethernet (1000Base-T), Hi-Speed USB 2.0 certified, FireWire (IEEE-1394a compliant) Adobe* PostScript* 3**, Adobe PDF 1.7, TIFF, JPEG, HP-GL/2, HP-RTL, CALS G4, HP PCL 3 GUI HP-GL/2, HP-RTL, and PostScript drivers for Windows* (optimized for AutoCAD 2000 and higher); PostScript drivers for Mac 05 X and Linux; support for Citrix XenApp and Citrix XenServer environments 1900 x 1000 x 1600 mm (74.8 x 39.4 x 63 in) 1930 x 766 x 1529 mm (75.98 x 30.16 x 60.2 in) 200 kg (440 lb) 280 kg (617 lb) er, printheads, introductory ink cartridges, printer stand, spindle, but posters, start-up software, scanner, touchscreen (panel PC) oftware, system recovery software, customer service guide, USE ernet cable, power cords 15 to 40°C (41 to 104°F) -25 to 55°C (-13 to 131°F) 20 to 80% RH 47 dB(A) (active); 32 dB(A) (standby) 6.3 B(A) (active); 4.4 B(A) (standby)
Print languages Drivers (included) MFP Shipping MFP Shipping X HP Designjet T1200 Print quick reference guides, st scanner documentation s cable, FireWire cable, Eth Operating temperature Storage temperature Operating humidity Sound pressure Sound power 120 watts (printing); 300 embedded Digital Front E Printer: input voltage (aut	certified, EIO Jetdirect accessory slot Scanner: Gigabit Ethernet (1000Base-T), Hi-Speed USB 2.0 certified, FireWire (IEEE-1394a compliant) Adobe* PostScript* 3™, Adobe PDF 1.7, TiFF, JPEG, HP-GL/Z, HP-RTL, CALS G4, HP PCL 3 GUI HP-GL/Z, HP-RTL, and PostScript drivers for Windows® (optimized for AutoCAD 2000 and higher); PostScript drivers for Mac OS X and Linux; support for Citrix XenApp and Citrix XenServer environments 1900 x 1000 x 1600 mm (74.8 x 39.4 x 63 in) 1930 x 766 x 1529 mm (75.98 x 30.16 x 60.2 in) 200 kg (440 lb) 280 kg (617 lb) er, printheads, introductory ink cartridges, printer stand, spindle, etup posters, start-up software, system recovery software, customer service guide, USE ernet cable, power cords 5 to 40°C (41 to 104°F) -25 to 55°C (-13 to 131°F) 20 to 80% RH 47 dB(A) (active); 32 dB(A) (standby) watts (scanning); 65.3 watts (ready); < 7 watts (< 25 watts with
Print languages Drivers (included) MFP Shipping MFP Shipping X HP Designjet T1200 Print quick reference guides, so scanner documentation s cable, FireWire cable, Eth Operating temperature Operating temperature Operating humidity Sound pressure Sound power 120 watts (printing); 300 embedded Digital Front E Printer: input voltage (aut max; Scanner: input voltage (aut	certified, EIO Jetdirect accessory slot Scanner: Gigabit Ethernet (1000Base-T), Hi-Speed USB 2.0 certified, FireWire (IEEE-1394a compliant) Adobe* PostScript* 3™, Adobe PDF 1.7, TiFF, JPEG, HP-GL/2, HP-RTL, CALS G4, HP PCL 3 GUI HP-GL/2, HP-RTL, and PostScript drivers for Windows* (optimized for AutoCAD 2000 and higher); PostScript drivers for Mac 05 X and Linux; support for Citrix XenApp and Citrix XenServer environments 1900 x 1000 x 1600 mm (74.8 x 39.4 x 63 in) 1930 x 766 x 1529 mm (75.98 x 30.16 x 60.2 in) 200 kg (440 lb) 280 kg (617 lb) er, printheads, introductory ink cartridges, printer stand, spindle, etup posters, start-up software, scanner, touchscreen (panel PC) oftware, system recovery software, customer service guide, USE ernet cable, power cords 5 to 40°C (41 to 104°F) -25 to 55°C (-13 to 131°F) 20 to 80% RH 47 dB(A) (active); 3.2 dB(A) (standby) 6.3 B(A) (active); 3.5 watts (ready); < 7 watts (< 25 watts with not) (sleep); 3.6 watts (off) to ranging) 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz), 2 A ge (auto ranging) 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 USA and Canada (CSA certified), EU (LVD and EN60950-1 compliant), Russia (GOST), Singapore (PSB), China (CCC),
Print languages Drivers (included) MFP Shipping MFP Shipping X HP Designjet T1200 Print quick reference guides, so scanner documentation scable, FireWire cable, Eth Operating temperature Storage temperature Operating humidity Sound pressure Sound power 120 watts (printing); 300 embedded Digital Front E Printer: input voltage (aut max; Scanner: input voltage Ita), 5 A max	certified, EIO Jetdirect accessory slot Scanner: Gigabit Ethernet (1000Base-T), Hi-Speed USB 2.0 certified, FireWire (IEEE-1394a compliant) Adobe* PostScript* 3™, Adobe PDF 1.7, TiFF, JPEG, HP-GL/2, HP-RTL, CALS G4, HP PCL 3 GUI HP-GL/2, HP-RTL, and PostScript drivers for Windows® (optimized for AutoCAD 2000 and higher); PostScript drivers for Mac 0S X and Linux; support for Citrix XenApp and Citrix XenServer environments 1900 x 1000 x 1600 mm (74.8 x 39.4 x 63 in) 1930 x 766 x 1529 mm (75.98 x 30.16 x 60.2 in) 200 kg (440 lb) 280 kg (617 lb) er, printheads, introductory ink cartridges, printer stand, spindle, stup posters, start-up software, scanner, touchscreen (panel PC) oftware, system recovery software, customer service guide, USE ernet cable, power cords 5 to 40°C (41 to 104°F) -25 to 55°C (-13 to 131°F) 20 to 80% RH 47 dB(A) (active); 3.2 dB(A) (standby) 6.3 B(A) (active); 3.5 watts (ready); < 7 watts (< 25 watts with nd) (sleep); 3.6 watts (off) to ranging) 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz), 2 A ge (auto ranging) 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 USA and Canada (CSA certified), EU (LVD and EN60950-1 compliant), Russia (GOST), Singapore (PSB), China (CCC), Argentina (IRAM), Mexico (NYCE), Korea (KATS) Compliant with Class A requirements, including USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand
Print languages Drivers (included) MFP Shipping MFP Shipping X HP Designjet T1200 Print quick reference guides, se scanner documentation scable, FireWire cable, Eth Operating temperature Operating temperature Operating humidity Sound pressure 120 watts (printing); 300 embedded Digital Front E Printer: input voltage (aut max; Scanner: input voltatl2), 5 A max Safety	certified, ElO Jetdirect accessory slot Scanner: Gigabit Ethernet (1000Base-T), Hi-Speed USB 2.0 certified, FireWire (IEEE-1394a compliant) Adobe* PostScript* 37*, Adobe PDF 1.7, TIFF, JPEG, HP-GL/Z, HP-RTL, CALS G4, HP PCL 3 GUI HP-GL/Z, HP-RTL, and PostScript drivers for Windows* (optimized for AutoCAD 2000 and higher); PostScript drivers for Mac OS X and Linux; support for Citrix XenApp and Citrix XenServer environments 1900 x 1000 x 1600 mm (74.8 x 39.4 x 63 in) 1930 x 766 x 1529 mm (75.98 x 30.16 x 60.2 in) 200 kg (440 lb) 280 kg (617 lb) er, printheads, introductory ink cartridges, printer stand, spindle, tup posters, start-up software, customer service guide, USiernet cable, power cords 5 to 40°C (41 to 104°F) -25 to 55°C (-13 to 131°F) 20 to 80% RH 47 dB(A) (active); 32 dB(A) (standby) watts (scanning); 65.3 watts (ready); < 7 watts (< 25 watts with nd) (sleep); 3.6 watts (off) or anging) 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz), 2 A ge (auto ranging) 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 USA and Canada (CSA certified), EU (LVD and EN60950-1 compliant), Russia (GOST), Singapore (PSB), China (CCC), Argentina (RAM), Mexico (NYCE), Korea (KATS) Compliant with Class A requirements, including USA (FCC rules),
	Margins (top x bottom x left x right) Technology Ink types Ink drop Line accuracy Minimum line width Guaranteed minimum line width Scan speed ³ Scan/copy resolution Max scan width Max scan thickness Reduction/enlargement Maximum copies Copier settings Handling Printer Scanner

Ordering information

oi uei iliy	1111 011	mation
Product	CQ653C7	HP Designjet T1200 HD Multifunction Printer
Accessories	Q6709A	HP Designjet 44-inch Roll Feed Spindle
	J8025A	HP Jetdirect 640n Print Server
	CN538A	HP Designjet 3-in Core Adapter
	A9D02A	SCP reprocontrol with Folder Driver for HP
Original HP	C9380A	HP 72 Gray and Photo Black Printhead
orintheads C9383A	C9383A	HP 72 Magenta and Cyan Printhead
	C9384A	HP 72 Matte Black and Yellow Printhead
Original HP	C9397A	HP 72 69-ml Photo Black Ink Cartridge
ink cartridges	C9398A	HP 72 69-ml Cyan Ink Cartridge
	C9399A	HP 72 69-ml Magenta Ink Cartridge
	C9400A C9401A C9403A C9370A C9371A C9372A C9373A	HP 72 69-ml Yellow Ink Cartridge
		HP 72 69-ml Gray Ink Cartridge
		HP 72 130-ml Matte Black Ink Cartridge
		HP 72 130-ml Photo Black Ink Cartridge
		HP 72 130-ml Cyan Ink Cartridge
		HP 72 130-ml Magenta Ink Cartridge
		HP 72 130-ml Yellow Ink Cartridge
C9374A	C9374A	HP 72 130-ml Gray Ink Cartridge
	CH575A	HP 726 300-ml Matte Black Ink Cartridge
Original HP large format printing	C1861A	HP Bright White Inkjet Paper (FSC* certified) [®] 🋟 [®] 914 mm x 45.7 m (36 in x 150 ft)
materials	C6567B	HP Coated Paper (PEFC™ certified) [®] ♣ 1067 mm x 45.7 m (42 in x 150 ft)
		HP Heavyweight Coated Paper (PEFC™ certified) ⁸ 🎝 1067 mm x 30.5 m (42 in x 100 ft)
	Q8809A	HP Premium Satin Photo Paper (FSC" certified) ⁸ 1067 mm x 22.9 m (42 in x 75 ft)
Service and support	UT911E	HP 3 year Next Business Day Onsite Support
	UT914E	HP 3 year Next Business Day Onsite Support with Defective Media Retention ¹⁰
	UT917E	HP 3 year 4 hour response, 9x5 Onsite Support ¹¹
	UT920E	HP 3 year 4 hour response, 13x5 Onsite Support ¹¹
	UT923PE	HP 1 year, Post Warranty, Next Business Day Onsite Support
	UT924PE	HP 2 year Post Warranty, Next Business Day Onsite Support
	UT925PE	HP 1 year Post Warranty, Next Business Day Onsite Support with Defective Media Retention ¹⁰
	UT926PE	HP 1 year Post Warranty, 4 hour response, 9x5 Onsite Support ¹¹
	UT927PE	HP 1 year Post Warranty, 4 hour response, 13x5 Onsite Support ¹¹
	H4518E	HP Network Installation Service Designjet 400-6100 SVC

HP Designjet Support Services offer solutions for business critical environments installation, extended support and maintenance, as well as variety of value added services. For more information, please visit https://dp.com/go/designjetsupport.

Use Original HP inks and printheads to experience consistent high quality and reliable performance that enable less downtime. These critical components are designed and engineered together as an optimized printing system to provide precise line accuracy as well as dark blacks and true neutral grays¹³ For more information, visit <u>hp.com/go/OriginalHPinks</u>.

For the entire HP Large Format Printing Materials portfolio, please see $\underline{\mathsf{globalBMG.com/hp.}}$

- Mechanical printing time. Printed on plain media with Economode on with Original HP inks.
- Mechanical printing time with Original HP inks. \pm /-0.1% of the specified vector length or \pm /-0.1 mm (whichever greater) at 23° C (73° F), 50 to 60% RH, on AO/E HP Matte Film in Best or Normal mode with Original HP inks.
- Measured on HP Matte Film.
- Measured in 200 dpi/400 dpi Turbo mode.
- Based on 384 MB RAM.
- CQ653C includes a Windows 7 panel PC. The HP Designjet T1200 printer is Windows 8 certified. FSC® trademark license code FSC®-C017543, see <u>fsc.org</u>. PEFC™ trademark license code PEFC™/29-31-198, see <u>pefc.org</u>. Not all FSC®- or PEFC™-certified products are available in all regions.
- Can be recycled through commonly available recycling programs. Not available in Europe, Middle East and Africa.
- Not available in North America and Latin America.
- Applicable to HP Designjet T-series Printers, ePrinters, and eMFPs. True neutral grays produced by printers compatible with the HP Three-black ink set.

















For more information, please visit

hp.com/go/DesignjetT1200HD-MFP



