

# HP LaserJet 3015 all-in-one printer/fax/scanner/copier



The HP LaserJet 3015 all-in-one is an affordable and compact sheetfed laser all-in-one that makes printing, faxing, colour scanning and digital copying easy and dependable.

**Ideal for users in small and medium sized businesses or in a home office environment who need one affordable, space-saving device that gives them the flexibility to print, fax, copy and scan, while also ensuring ease-of-use and reliable production of professional documents.**

**Expect great performance from this impressively low-priced printer, fax, copier and colour scanner.**

- Save time and money: the affordably priced HP LaserJet 3015 prints and copies documents quickly and easily at up to 14 ppm.
- No waiting for your prints: first page out in just 10 seconds thanks to Instant-on Technology.
- Produce crisp and sharp laser documents at 1200 dpi\* effective output quality.
- Fast and advanced faxing at 33.6 Kbps, including delayed faxing and fax to PC\*\*.
- Handle complex jobs with 32 MB RAM and an additional 2 MB fax memory for storing 110 pages of fax documents.

**This HP LaserJet all-in-one's small footprint fits easily wherever you want it.**

- The HP LaserJet 3015 all-in-one gives you a complete office solution with high quality prints, faxes, colour scans and digital copies from one compact device.
- Thanks to the sheetfed design and the small footprint you can place this versatile appliance exactly where you need to – and save precious office space.

**Easy to use with an intuitive user interface and software as well as easy-to-replace supplies.**

- HP Toolbox software with single-click access to all functions enables simple configuration, status and support.
- Optical Character Recognition (OCR) software lets you convert hardcopy documents into editable electronic files.
- Efficient multi-tasking: use functions simultaneously.
- Simple and clean supplies installation and replacement due to all-in-one cartridge design.
- Robust 7,000 page per month duty cycle and proven HP LaserJet quality.

\*600 x 600 dpi with HP Resolution Enhancement technology (RET) and FastRes 1200.

\*\* Fax to PC available with Microsoft® Windows®.

## Technical specifications

<b>Print speed</b>	Up to 14 ppm First page out: 10 secs for printing (Instant-on Technology virtually eliminating warm-up time – from cold or warm start) (Exact speed varies depending on the system configuration, software program, and document complexity)		
<b>Processor</b>	240 MHz, Motorola Coldfire <sup>®</sup> v 4e		
<b>Memory</b>	32 MB RAM		
<b>Print quality</b>	1200 dpi effective output quality [600 x 600 dpi with HP Resolution Enhancement technology (REt) and FastRes 1200 technology]		
<b>Print margins (A4)</b>	Top: 4.2 mm, left: 4.2 mm, right: 4.2 mm, bottom: 4.2 mm		
<b>Print</b>	Technology:	Monochrome Laser	
	Languages:	HP PCL 6, HP PCL 5e, HP Postscript Level 2 Emulation	
	Economical printing:	Economode print-quality setting prints text with less toner. This setting is useful when printing drafts. This setting can be used independently of other print-quality settings.	
	Typefaces/fonts:	PCL: 45 scalable TrueType fonts, PostScript: 35 scalable TrueType fonts	
	Duty cycle:	Up to 7,000 pages per month	
<b>Fax</b>	Modem:	33.6 Kbps (3 secs per page)	
	Telecom:	TBR21: 1998; EG 201 121: 1998, FCC Part 68	
	Memory:	Up to 110 pages (2 MB)	
	Resolution:	Standard: 203 x 98 dpi, fine: 203 x 196 dpi, superfine: 300 x 300 dpi (no halftone), photo: 300 x 300 dpi (halftone enabled)	
	Quick dialing:	120 numbers, 7 one-touch front panel keys	
<b>Scan</b>	Type:	ADF, colour scanning	
	Resolution:	600 x 600 dpi optical, 9600 x 9600 dpi enhanced	
	Bit depth:	24-bit	
	Levels of grey:	256	
	Twain version:	Twain compatible version 1.9	
	Scannable area:	Minimum media size: 74 x 105 mm (from ADF), maximum media size: 216 x 381 mm (from ADF)	
	Margins for scanned items:	Left: 4.2 mm, top: 4.2 mm, right: 4.2 mm, bottom: 5.0 mm	
<b>Copy</b>	Speed:	Up to 14 cpm	
	Multiple copies:	1-99 copies, with automatic collation	
	Reduce/enlarge:	25 to 400% (1% increments)	
<b>Media handling</b>	<b>Input</b>	<b>Weight</b>	<b>Size</b>
	Tray 1	Input tray: 60 to 163 g/m <sup>2</sup> (recommended: 75 to 90 g/m <sup>2</sup> ); automatic document feeder (ADF): 42 to 260 g/m <sup>2</sup> ; output bin: 60 to 163 g/m <sup>2</sup>	Standard: A4, A5, Letter, Legal, B5, C5, C6, DL; 76 x 127 to 216 x 356 mm; automatic document feeder (ADF): A4, A5; 74 x 105 to 216 x 381 mm
	<b>Capacity:</b>	150 (main input tray), 10 (priority feed), 30 (ADF)	
	<b>Output:</b>	Sheets: 125, envelopes: 15, transparencies: 10	
	<b>Duplex printing:</b>	Manual (driver support provided)	
<b>Media types</b>	Paper (plain, preprinted, prepunched, bond, colour, glossy, letterhead, light, heavy, recycled, rough), envelopes, transparencies, labels, cardstock		
<b>Interface and connectivity</b>	USB port – compatible with 2.0 specifications; parallel port – IEEE 1284-B Optional: HP Jetdirect external print servers and wireless print servers: HP Jetdirect 170x, 175x, 300x, 380x, 500x, en3700, bi1300		
<b>Operating systems compatibility</b>	Microsoft <sup>®</sup> Windows <sup>®</sup> 98 Second Edition, 2000, Me, XP; Windows NT <sup>®</sup> 4.0 print driver only; Mac OS 9.1, 9.2.x, Mac OS X v10.2.x available on web; DOS, Linux, UNIX, OS/2 print functionality only available on web Latest drivers available from <a href="http://www.hp.com">http://www.hp.com</a>		
<b>Network operating systems compatibility</b>	Optional: Via HP Jetdirect 170x print server: Microsoft <sup>®</sup> Windows <sup>®</sup> 98, NT 4.0, 2000, Novell <sup>™</sup> NetWare 3.2, 4.2, 5.x; via HP Jetdirect 175x print server: Microsoft Windows 98, Me, NT 4.0, 2000, XP, XP 64-bit, Server 2003, Apple Mac OS 8.6 and later; via HP Jetdirect 300x, 500x print servers: Microsoft Windows 98, Me, NT 4.0, 2000, XP, Novell NetWare 3.2, 4.2, 5.x, 6, Apple Mac OS 8.6 and later, Red Hat Linux 6.x and later, SuSE Linux 6.x and later, HP-UX 10.20, 11.x, Solaris <sup>™</sup> 2.5x, 2.6, 7, 8 (SPARC systems only), IBM <sup>®</sup> AIX 3.2.5 and later, MPE-iX; via HP Jetdirect 380x, en3700 print servers: Microsoft Windows 98, Me, NT 4.0, 2000, XP, XP 64-bit, Server 2003, Novell NetWare 3.2, 4.2, 5.x, 6, Apple Mac OS 8.6 and later, Red Hat Linux 6.x and later, SuSE Linux 6.x and later, HP-UX 10.20, 11.x, Solaris 2.5x, 2.6, 7, 8 (SPARC systems only), IBM AIX 3.2.5 and later, MPE-iX		
<b>Minimum system requirements</b>	Windows <sup>®</sup> 98: Pentium <sup>®</sup> processor or better, 24 MB RAM; Windows Me: Pentium 150 MHz or better, 32 MB RAM; Windows NT <sup>®</sup> 4.0: Pentium or better, 32 MB RAM; Windows 2000: Pentium 133 MHz or better, 64 MB RAM; Windows XP: Pentium 300 MHz or better, 128 MB RAM Mac 9.1: Mac OS-based Apple computer with a PowerPC microprocessor, at least 32 MB of RAM with virtual memory set to 64 MB; Mac 9.2.x: Power Mac G4 or Macintosh Server G4 (all models), Power Macintosh G3 or Macintosh Server G3 (all models), iMac (all models), iBook (all models), Powerbook (all models later than the original PowerBook G3), at least 32 MB RAM with virtual memory set to 64 MB; Mac OS X v 10.2.x: Power Mac G5 (all models), Power Mac G4 or Macintosh Server G4 (all models), Power Macintosh G3 or Macintosh Server G3 (all models), iMac (all models), iBook (all models), Powerbook (all models later than the original PowerBook G3), 128 MB RAM		
<b>Standard software</b>	HP Toolbox, HP LaserJet Scan, TWAIN or WIA Scan Driver, HP LaserJet Fax, Readiris OCR (not installed with other software; separate installation required), printer drivers (HP PCL 6, HP PCL 5e, HP Postscript Level 2 Emulation), installer/uninstaller, HP Director (Macintosh), HP all-in-one Setup Assistant		
<b>Control panel</b>	Fax controls, alphanumeric buttons, menu and cancel controls, copy controls, scan controls, 2 line x 16-character display		
<b>Printer management</b>	HP Toolbox; HP Web Jetadmin, Embedded Web Server (with optional HP Jetdirect external print servers)		
<b>Power requirements</b>	Input voltage 220 to 240 VAC (± 10%), 50/60 Hz (± 2 Hz), 2.3 amp		
<b>Power consumption</b>	260 watts maximum (printing), 7 watts (standby and PowerSave), 0 watt (off)		
<b>Dimensions (w x d x h)</b>	Out of package: 426 x 470 x 445 mm, packaged: 600 x 400 x 475 mm		
<b>Weight</b>	Out of package: 9.5 kg, packaged: 11.6 kg		
<b>Operating environment</b>	Environmental ranges: Operating temperature: 15 to 32.5° C, operating humidity: 10 to 80% RH, storage temperature: -20 to 40° C, storage humidity: 0 to 95% RH. Noise level per ISO 9296: sound power: LwAd 6.2 B(A) LwAd (printing at 14 ppm), sound pressure: LpAm 56 dB(A) (operator position), 49 dB(A) (bystander)		
<b>Product certifications</b>	Safety certifications: IEC 60950: 1999/EN 60950: 2000; IEC 60825-1: 1993 + A1: 1996 + A2: 2001/EN 60825-1: 1994 + A11: 1996 + A2: 2001 (Class 1 Laser/LED Product); GB4943-1995. EMC certifications: CISPR 22: 1998/EN 55022: 1998 – Class B; EN 61000-3-2: 1995/A14:2000; EN 61000-3-3: 1995; EN 55024: 1998; FCC Title 47 CFR, Part 15 Class B 2/ICES-003, Issue 3; GB9254-1998. Energy Star <sup>®</sup>		
<b>Warranty</b>	One-year limited warranty covers HP hardware, software, accessories, and supplies		

<http://www.hp.com>

For more information, please call your local HP sales office or representative: **Austria:** 0800 242 242, **Algeria:** (0)61 56 45 43, **Bahrain:** 800 728, **Belgium:** (078) 15 20 30 (0.0496 EUR/min), **Bulgaria:** (+359) 2960 1940, **Croatia:** (+385 1) 60 60 200, **Czech Republic:** (00 420 2) 261 108 108 (Prague), **Denmark:** 45991700 or 70101125, **Egypt:** 532 5222, **Estonia:** (+372) 6813 823, **Finland:** (+358) 0205350 or 0205 350, **France:** (1) 69 82 6060, **Germany:** 0180 532 6222 (12 Cent/min), **Greece:** (01) 678 96 00, **Hungary:** (+36) 1 382-1111, **Iceland:** (354) 570 1000, **Ireland:** + 353 1 6158200, **Israel:** (972) 9 8304848, **Italy:** (02) 92121, **Kazakhstan:** +7 (3272) 980 824, **Latvia:** (371) 800 80 12, **Lithuania:** 8 800 10000 or 8 5 2103333, **Luxembourg:** (+352) 263 160 34, **Middle East:** 00971 4 883 4427, **Morocco (African Region):** +212 22 40 47 47, **Netherlands:** (020) 5476666, **Norway:** 22 735600, **Poland:** infolinia: 0-800 122 622, **Portugal:** (808) 206 001, **Romania:** (+401) 205 3300, **Russia:** +7 (095) 797 35 00, **Saudi Arabia:** 800 124 4646, **Serbia/Montenegro:** +381 11 334 21 02, **Slovakia:** +421-2-50222111, **Slovenia:** +386 1 2307 420, **South Africa:** 0800 118 883, **Spain:** (91) 634 88 00, **Sweden:** (08) 444 2000, **Switzerland:** 0848 88 44 66, **Tunisia:** 71 891 222, **Turkey:** +90 (216) 579 71 71, **UAE:** 8004910, **UK:** 08705 474747, **Ukraine:** +380 44 490 61 20.



©2004 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP Products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Published in EMEA 02/04 59823616EEE

## Ordering information

<b>Q2669A</b>	HP LaserJet 3015 all-in-one printer/fax/scanner/copier, HP LaserJet print cartridge, getting started guide, fax guide, device software including Optical Character Recognition (OCR) software and electronic user's guide on CD-ROM, 150-sheet media input tray, ADF input tray, ADF output support, output bin support, power cord, phone cord
---------------	---

### Supplies

<b>Q2612A</b>	HP Ultracrisse Standard Capacity Print Cartridge, black (up to 2,000 pages*)
---------------	--

### Cables

<b>C6518A</b>	HP USB cable – 2 m
<b>C2950A</b>	HP IEEE parallel cable (B-type) – 2 m
<b>C2951A</b>	HP IEEE parallel cable (B-type) – 3 m

### HP Jetdirect external print servers

<b>J3258B</b>	HP Jetdirect 170x external print server (parallel/10BT)
<b>J6035C</b>	HP Jetdirect 175x external print server (USB-10/100Base-TX)
<b>J3263A</b>	HP Jetdirect 300x external print server (parallel/10/100TX)
<b>J6061A</b>	HP Jetdirect 380x wireless external print server (USB – 802.11b)
<b>J3265A</b>	HP Jetdirect 500x external print server (3 port parallel-10/100Base-TX/10Base2)
<b>J7942A</b>	HP Jetdirect en3700 external print server
<b>J6072A</b>	HP BT1300 Bluetooth <sup>®</sup> Wireless Printer Adapter (for USB or parallel)

### Service & support

<b>U9811A/E</b>	HP Care Pack – next business day on-site response, 3 years
<b>U9809A/E</b>	HP Care Pack – return to HP, 3 years
<b>U9813PA/PE</b>	HP Care Pack – post warranty, next business day on-site response, 1 year

\* Based on 5% coverage

