

MC2325adw

Reliability. Security. Productivity.















Lexmark MC2325adw

Reliable, productive and secure multifunction color is within reach of any budget with the Lexmark MC2325, featuring output up to 25 pages per minute*. It reliably handles diverse media types and sizes and comes equipped with both built-in Wi-Fi and tools to help you minimize toner consumption.



Ready when you are

- 1.2-GHz quad-core processor and 1 GB memory drives printing at up to 25 ppm.*
- Scan at up to 50 pages per minute.
- Steel frame and durable design stands up to heavy use and harsh environments.
- ▶ Long-life fuser and imaging components extend uptime.
- Vinison[™] Toner replacement cartridges deliver up to 2300 color and 3000 monochrome pages**.
- ▶ Keep printing in black even when color toner is empty.

Color that keeps saving

- PANTONE® calibration, embedded color sample pages and Lexmark Color Replacement produce accurate, professional color output in-house.
- Save toner with suite of tools that let you choose when and how much color to print.

Input that works

- Reliable, flexible media handling supports cardstock, small media, and envelopes from the main tray or a convenient single-sheet feeder.
- ▶ Get 251 pages of total input.

Interact with ease

- 2.4-inch/6-cm color LCD lets you configure, interact and monitor vital system information.
- Front USB port allows walk-up printing from popular file formats without a computer.
- Compact footprint allows flexible placement in more locations.
- Connect easily via Ethernet, USB, Wi-Fi or simple mobile printing options.

Full-spectrum security

- Lexmark's full-spectrum security architecture helps keep your information safe—in the document, on the device and over the network.
- Keypoint Intelligence Buyers Lab honored Lexmark with a prestigious BLI PaceSetter award for Document Imaging Security***.



Built for planet earth

- Energy management features reduce power consumption in active use or sleep mode.
- Standard two-sided printing saves paper.
- Recycle cartridges through the award-winning Lexmark Cartridge Collection Program (LCCP).

^{*}Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: www.lexmark.com/ISOspeeds.

**Average continuous black or continuous composite color (CMY) declared yield in one-sided (simplex) mode up to this number of pages in accordance with ISO/IEC 19798. Actual yield will vary considerably based upon many factors. See www.lexmark.com/yields for more information.

***Award based on North America and/or Western Europe data



Lexmark MC2325adw



Mutifunction product with 2.4-inch/6-cm LCD 18.2 x 17.4 x 21.9 inches 462 x 442 x 556 mm Adjustable printer stand (not shown) 20.5 x 25.7 x 24.6 inches 521 x 653 x 625 mm

Swivel cabinet (not shown) 10.4 x 18.7 x 23.6 inches 263 x 476 x 600 mm



Note 1: Does not support optional trays.

Note 2: All measurements are shown as height x width x depth. For more information about supported configurations, refer to the Printer, Option and Stand Compatibility Guide at http://www.lexmark.com/publications/furniture_safety/

 $\ensuremath{\texttt{@}}$ 2018 Lexmark. All rights reserved.

Lexmark, the Lexmark logo and Unison are trademarks of Lexmark International, Inc., registered in the United States and/or other countries. AirPrint and the AirPrint Logo are trademarks of Apple, Inc. Google Cloud Print is a trademark of Google, Inc. MOPRIA®, the Mopria® Logo™ and the Mopria® Alliance logos are trademarks, service marks, and certification marks of Mopria Alliance, Inc. in the United States and other countries. PANTONE® Goe™ and other Pantone, Inc. trademarks are property of Pantone, Inc. All other trademarks are the property of their respective owners.

This product includes software developed by the OpenSSL Project for use in the Open SSL Toolkit (http:// ww.openssl.org/).



Product specifications	Lexmark MC2325adw
Printing	
Display	2.4-inch (60 mm) Color LCD display
Print Speed: Up to ⁶	Black: 25 ppm / Color: 25 ppm
Time to First Page: As fast as	Black: <11.7 seconds / Color: <11.7 seconds
Print Resolution	Black: 1200 x 1200 dpi, 4800 Color Quality (2400 x 600 dpi) / Color: 1200 x 1200 dpi, 4800 Color Quality (2400 x 600 dpi)
Memory	Standard: 1024 MB / Maximum: 1024 MB
Hard Disk	Not Available
Recommended Monthly Page Volume ²	500 - 5000 pages
Maximum Monthly Duty Cycle: Up to ³	60000 pages per month
Copying	
Copy Speed: Up to ⁶	Black: 25 cpm / Color: 25 cpm
Time to First Copy: As fast as	Black: 12 seconds / Color: 12.5 seconds
Scanning	
Scanner Type / ADF Scan	Flatbed scanner with ADF / Simplex
A4/Ltr Simplex Scan Speed: Up to	Black: 47/50 sides per minute / Color: 30/32 sides per minute
ADF Paper Input Capacity: Up to	50 pages 20 lb or 75 gsm bond
Faxing	
Modem Speed	Max is 33,600 bps, V.34 Half-Duplex Kbps
Supplies ⁷	
Laser Cartridge Yields (up to) ¹	1,000-page Black and Color (CMYK) Cartridges, 2,300-page Colour (CMY) High Yield Cartridges, 3,000-page Black High Yield Cartridge
Photoconductor Estimated Yield: Up to⁵	40,000 pages, based on 3 average letter/A4-size pages per print job and ~ 5% coverage
Cartridge(s) Shipping with Product ¹	1,400-page Black Starter Return Program Toner Cartridge, 750-page Color (CMY) Starter Return Program Toner Cartridge
Paper Handling	
Included Paper Handling	250-Sheet Input, 150-Sheet Output Bin, Integrated Duplex, Single-Sheet Manual Feed
Paper Input Capacity: Up to	Standard: 250+1 pages 20 lb or 75 gsm bond / Maximum: 250+1 pages 20 lb or 75 gsm bond
Paper Output Capacity: Up to	Standard: 150 pages 20 lb or 75 gsm bond / Maximum: 150 pages 20 lb or 75 gsm bond
Media Types Supported	Card Stock, Paper Labels, Plain Paper, Vinyl Labels, Refer to the Paper & Specialty Media Guide
Media Sizes Supported	10 Envelope, 7 3/4 Envelope, 9 Envelope, A4, A5, B5 Envelope, C5 Envelope, DL Envelope, Hagaki Card, Executive, Folio, JIS-B5, Legal, Letter, Statement, Universal, Oficio, A6
General Information ⁴	
Standard Ports	USB 2.0 Specification Hi-Speed Certified (Type B), Gigabit Ethernet (10/100/1000), 802.11b/g/n Wireless, Front Hi-Speed USB Port Compatible with USB 2.0 Specification (Type A)
Optional Network Ports	Marknet N8372 WiFi Option
Noise Level: Operating	Print: 49 dBA / Copy: 55 dBA / Scan: 54 dBA
Specified Operating Environment	Humidity: 8 to 80% Relative Humidity, Temperature: 10 to 32°C (50 to 90°F), Altitude: 0 - 2896 Meters (9,500 Feet)
Limited Warranty - See Statement of Limited Warranty	1-Year Onsite Service, Next Business Day
Size (in H x W x D) / Weight (lb.)	18.2 x 17.4 x 21.9 in. / 58 lb.

All information in this brochure is subject to change without notice. Lexmark is not liable for any errors or omissions.

¹Average continuous cartridge yield is stated number of standard pages as listed. Declared yield value in accordance with ISO/IEC 19798. ²"Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage. ³"Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs. ⁴Printers are sold subject to certain license/agreement conditions. See www.lexmark.com/printerlicense for details. ⁵Actual Yield may vary based on other factors such as device speed, paper size and feed orientation, toner coverage, tray source, percentage of black-only printing and average print job complexity. ⁴Print and copy speeds measured in accordance with ISO/IEC 24735 respectively (ESAT). For more information see: www.lexmark.com/ISOspeeds. ⁵Product functions only with replacement cartridges designed for use in a specific geographical region. See www.lexmark.com/regions for more details.

