



# Lexmark MC3224adwe

**Small. Dependable. Secure.**

Compact and lightweight, the Lexmark MC3224adwe multifunction brings color printing, scanning, copying, faxing and touch-screen convenience to small workgroups. It offers color output at up to 24 pages per minute\* in a package that fits almost anywhere. There's Wi-Fi to support mobile users and Lexmark full-spectrum security is built in.



## Compact color versatility

- ▶ Get color output at up to 24 pages per minute\*, plus automatic-feed single-side scanning and analog faxing.
- ▶ Tackle your printing workload with the power of a 1-GHz processor and 512 MB of memory.
- ▶ Connect via standard Wi-Fi, ethernet and USB.
- ▶ Simplify mobile printing via Lexmark Mobile Print app, as well as Mopria® and AirPrint technologies.
- ▶ 2.8-inch (7.2 cm) touch screen offers built-in workflow capabilities like scan to network, scan to email and Lexmark's own Cloud Connector\*\*\*\*.

## Easy to set up, easy to keep going

- ▶ Compact dimensions of 13.6 inches high x 16.2 inches wide x 15.5 inches deep (344.4 mm high x 411.2 mm wide x 394.1 mm deep) helps it fit almost anywhere.

- ▶ Unison™ Toner replacement cartridges deliver up to 1500 pages\*\* of high-quality output.
- ▶ Steel frame and lifetime imaging components mean long life and minimal maintenance.

## Robust, built-in security

- ▶ Lexmark's full-spectrum security architecture helps keep your information safe—on the document, the device, over the network, and everywhere in between.

## Built for planet earth

- ▶ Built-in energy-saving mode goes from sleep to print to sleep with nothing to set.
- ▶ Printer is rated EPEAT® Silver\*\*\* and is ENERGY STAR® certified.
- ▶ Recycle cartridges through the award-winning Lexmark Cartridge Collection Program (LCCP).



\* Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: [www.lexmark.com/ISOspeeds](http://www.lexmark.com/ISOspeeds).

\*\* Average continuous black or continuous composite color (CMY) declared yield in one-sided (simplex) mode up to this number of pages in accordance with ISO/IEC 19798. Actual yield will vary considerably based upon many factors. See [www.lexmark.com/yields](http://www.lexmark.com/yields) for more information.

\*\*\* EPEAT ratings may vary by location See [www.epeat.net](http://www.epeat.net) for registration status by country

\*\*\*\* Cloud Connector feature is available by end of 2019. Devices purchased prior to availability can get this feature via free firmware update at [support.lexmark.com/firmware](http://support.lexmark.com/firmware).

| Product Specifications                      |  | Lexmark MC3224adwe |
|---|--|--------------------|
| <b>Printing</b>                             |  |                    |
| Display                                     | 2.8 inch (7.2 cm) LCD touch panel  |                    |
| Print Speed                                 | Up to: Black: 24 ppm <sup>1</sup> (Letter) / Color: 24 ppm <sup>1</sup> (Letter)   |                    |
| Time to First Page                          | As fast as: Black: 11 seconds / Color: 11 seconds  |                    |
| Print Resolution                            | Black: 4800 Color Quality, 600 x 600 dpi / Color: 4800 Color Quality, Up to 600 x 600 dpi  |                    |
| Memory                                      | Standard: 512 MB / Maximum: 512 MB   |                    |
| Hard Disk                                   | Not Available  |                    |
| Recommended Monthly Page Volume             | 600 - 2000 pages <sup>2</sup>  |                    |
| Maximum Monthly Duty Cycle                  | Up to: 40000 pages per month <sup>3</sup>  |                    |
| <b>Copying</b>                              |  |                    |
| Copy Speed                                  | Up to: Black: 24 cpm <sup>1</sup> (Letter) / Color: 24 cpm <sup>1</sup> (Letter)   |                    |
| Time to First Copy                          | As fast as: Black: 13.4 seconds / Color: 13.4 seconds  |                    |
| <b>Scanning</b>                             |  |                    |
| Scanner Type / ADF Scan                     | Flatbed scanner with ADF / Simplex   |                    |
| A4/Ltr Simplex Scan Speed                   | Up to: Black: 20 / 21 sides per minute / Color: 20 / 21 sides per minute   |                    |
| ADF Paper Input Capacity                    | Up to: 50 pages 20 lb or 75 gsm bond   |                    |
| <b>Faxing</b>                               |  |                    |
| Modem Speed                                 | Max is 33,600 bps, V.34 Half-Duplex Kbps   |                    |
| <b>Supplies<sup>4</sup></b>                 |  |                    |
| Laser Cartridge Yields                      | up to: 1,500 <sup>5</sup> -page Black and Color (CMYK) Cartridges  |                    |
| Cartridge(s) Shipping with Product          | 750 <sup>5</sup> -page Black Starter Return Program Toner Cartridge, 500 <sup>5</sup> -page Color (CMY) Starter Return Program Toner Cartridge                                 |                    |
| <b>Paper Handling</b>                       |  |                    |
| Included Paper Handling                     | 100-Sheet Output Bin, Integrated Duplex, Single-Sheet Manual Feed, 250-Sheet Input   |                    |
| Paper Input Capacity                        | Up to: Standard: 250+1 pages 20 lb or 75 gsm bond / Maximum: 250+1 pages 20 lb or 75 gsm bond  |                    |
| Paper Output Capacity                       | Up to: Standard: 100 pages 20 lb or 75 gsm bond / Maximum: 100 pages 20 lb or 75 gsm bond  |                    |
| Media Types Supported                       | Hagaki Card, Paper Labels, Card Stock, Plain Paper, Glossy Paper, Refer to the Paper & Specialty Media Guide   |                    |
| Media Sizes Supported                       | A6, Oficio, 7 3/4 Envelope, 9 Envelope, JIS-B5, A4, Legal, A5, Hagaki Card, Letter, B5 Envelope, Statement, C5 Envelope, Executive, Universal, DL Envelope, Folio, 10 Envelope |                    |
| <b>General Information<sup>6</sup></b>      |  |                    |
| Standard Ports                              | Front Hi-Speed USB Port Compatible with USB 2.0 Specification (Type A), 802.11b/g/n Wireless, USB 2.0 Specification Hi-Speed Certified (Type B), Ethernet 10/100BaseTX (RJ-45) |                    |
| Noise Level                                 | Operating: 49 dBA (Print) / 49 dBA (Copy) / 44 dBA (Scan)  |                    |
| Specified Operating Environment             | Humidity: 8 to 80% Relative Humidity / Altitude: 0 - 3048 Meters (10,000 Feet) / Temperature: 10 to 32°C (50 to 90°F)  |                    |
| Limited Warranty                            | See Statement of Limited Warranty: 1-Advanced Exchange, 3-5 Business Day Ground Shipment   |                    |
| Size / Weight                               | H x W x D: 13.6 x 16.2 x 15.5 in. / 42.7 lb.   |                    |
| ENERGY STAR Typical Electricity Consumption | TEC: 0.34 kilowatt-hours per week  |                    |

All information is subject to change without notice. Lexmark is not liable for any errors or omissions.

<sup>1</sup> Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: [www.lexmark.com/ISOspeeds](http://www.lexmark.com/ISOspeeds).

<sup>2</sup> "Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage. <sup>3</sup> "Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs. <sup>4</sup> Product functions only with replacement cartridges designed for use in a specific geographical region. See [www.lexmark.com/regions](http://www.lexmark.com/regions) for more details. <sup>5</sup> Average continuous cartridge yield is stated number of standard pages as listed. Declared yield value in accordance with ISO/IEC 19798. <sup>6</sup> Printers are sold subject to certain license/agreement conditions. See [www.lexmark.com/printerlicense](http://www.lexmark.com/printerlicense) for details.

© 2019 Lexmark. All rights reserved.

Lexmark, the Lexmark logo and Unison are trademarks of Lexmark International, Inc., registered in the United States and/or other countries. AirPrint and the AirPrint Logo are trademarks of Apple, Inc. Google Cloud Print™ is a trademark of Google, LLC. Mopria®, the Mopria® Logo™ and the Mopria® Alliance logos are registered trademarks and service marks of Mopria Alliance, Inc. in the United States and other countries. Unauthorized use is strictly prohibited. All other trademarks are the property of their respective owners. This product includes software developed by the OpenSSL Project for use in the Open SSL Toolkit (<http://www.openssl.org/>).



[lexmark.com](http://lexmark.com)