

## Lexmark E232 Laser Printer



# Value

Up to 22 ppm printing

Sturdy industrial design with a small footprint

Compatible with multiple operating systems

PC and Mac compatible in a broad range of environments

USB and parallel ports standard



**LEXMARK**<sup>TM</sup>

# Lexmark

# E232



Lexmark E232



Lexmark E232t

## Ease of use

---

Intuitive status panel and easy paper loading for straight-forward installation and operation.

---

Toner low indicator, toner saver mode and job cancel button help you save time and money.

---

Parallel and USB standard.

---

Two-piece toner cartridge and photoconductor imaging system is clean and easy to install and replace.

---

Photoconductor kit lasts up to 30,000 pages.

---

## Reliability

---

Robust design supports up to 10,000 pages per month.

---

Integrated paper drawer for reliable paper feed.

---

Sturdy industrial design with a small footprint for use in areas where space is limited.

---

## Performance

---

Up to 22 ppm printing.

---

< 8.5 seconds time to first page.

---

200 MHz processor and 16MB memory.

---

## Print Quality

---

Adjustable print resolution settings let you optimize print quality and performance.

---

High-quality results on various media weights and types.

---

# The easy-to-use desktop laser printer providing professional results for personal or business applications.

		<b>Lexmark E232, E232t</b>	
<b>Part Number</b>	US/Canada: 22S0200 (E232), 22S0270 (E232t)		
<b>Technology</b>	Monochrome laser		
<b>Speed</b>	Up to 22 ppm		
<b>Resolution</b>	2400 image quality, 1200 image quality, 600 x 600 dpi		
<b>Time to First Page</b>	< 8.5 seconds		
<b>Processor</b>	200 MHz		
<b>Memory (std./max.)</b>	16MB/80MB		
<b>Connectivity</b>	Bidirectional parallel port and USB port MarkNet™ X2000 series of external print servers <sup>2</sup> ; N4000e Ethernet print server <sup>3</sup> ; External serial adapter <sup>2</sup>		
<b>Operating Systems</b>	Microsoft Windows 98SE, Me, NT 4.0, 2000, XP and Server 2003; Linux; Mac OS For a complete list, visit <a href="http://www.lexmark.com">www.lexmark.com</a>		
<b>Emulations</b>	PCL 6 emulation		
<b>Fonts</b>	17 scalable including OCR-A, OCR-B and Code 3 of 9 bar codes. Bitmapped: 2		
<b>Paper Capacity (sheets)</b>		<b>E232</b>	<b>E232t</b>
Input: Standard		250 + 1	250 + 550 + 1
Maximum		250 + 550 + 1	250 + 550 + 1
Output: Standard		150 + 1	150 + 1
Maximum		150 + 1	150 + 1
<b>Paper Handling</b>			
Standard		E232: 250-sheet input drawer, 150-sheet output bin	
Optional		E232t: 250-sheet input drawer, 550-sheet input drawer, 150-sheet output bin	
		E232: 250-sheet input tray, 550-sheet input drawer, 550-sheet input tray	
		E232t: 250-sheet input tray, 550-sheet input tray	
<b>Paper Sources</b>		<b>E232</b>	<b>E232t</b>
Input: Standard		2	3
Maximum		3	3
Output: Standard		2	2
Maximum		2	2
<b>Media Types</b>	Plain paper, card stock, envelopes, transparencies and paper labels		
<b>Media Sizes</b>	Letter, legal, A4, A5, B5, executive, universal, statement and folio		
<b>Media Weights</b>	Plain paper: 16-24 lb. (60-90 g/m <sup>2</sup> ) Card stock: up to 90 lb. index (163 g/m <sup>2</sup> )		
<b>Size (W x D x H)</b>	E232: 15.6 in. x 13.9 in. x 9.8 in. (396.2 mm x 353.1 mm x 248.9 mm) E232t: 15.6 in. x 14.8 in. x 14.9 in. (396.0 mm x 376.0 mm x 381.9 mm)		
<b>Weight</b>	E232: 22 lb. (9.98 kg) E232t: 31 lb. (14.0 kg)		
<b>Acoustics</b>	51 dBA printing; 30 dBA idle		
<b>Supplies<sup>1</sup></b>	Ships with: 1,500-page Starter Return Program Toner Cartridge and up to 30,000-page Photoconductor kit Supplies: 2,500-page Return Program Toner Cartridge 2,500-page Toner Cartridge Up to 30,000-page Photoconductor kit		
<b>Duty Cycle</b>	Up to 10,000 pages per month		
<b>Warranty</b>	1-year limited warranty (3 to 5 business day exchange)		

<sup>1</sup> Yield is based on approximately 5% print coverage

<sup>2</sup> Connected through parallel port

<sup>3</sup> Connected through USB port

# Order Information Chart

Part No.	UPC	Description
<b>US/Canada</b>		
22S0200	7-34646-01600-1	Lexmark E232
22S0270	7-34646-01670-4	Lexmark E232t
<b>SUPPLIES</b>		
<b>Print Cartridges<sup>1</sup></b>		
12A8400	7-34646-38629-6	2,500-page Return Program Toner Cartridge
12A8300	7-34646-38626-5	2,500-page Toner Cartridge
<b>Other Supplies</b>		
12A8302	7-34646-38627-2	30,000-page Photoconductor Kit
<b>Media</b>		
70X7240	7-34646-03810-2	Transparencies (Letter, 50 sheets)
12A5010	7-34646-13899-4	Transparencies (A4, 50 sheets)
<b>OPTIONS AND FEATURES</b>		
<b>Paper Handling Options</b>		
22S0300	7-34646-02415-0	250-Sheet Tray
22S0301	7-34646-02416-7	550-Sheet Tray
22S0302	7-34636-02417-4	550-Sheet Drawer
<b>Memory Options</b>		
16H0056	7-34646-24756-6	16MB SDRAM
16H0057	7-34646-24757-3	32MB SDRAM
16H0058	7-34646-24758-0	64MB SDRAM

Part No.	UPC	Description
<b>NETWORK CONNECTIONS</b>		
<b>External Print Servers</b>		
46D0060	7-34646-30316-3	MarkNet X2011e Ethernet 10/100BaseTX – 1-port <sup>2</sup>
46D0040	7-34646-30315-6	MarkNet X2012e Ethernet 10/100BaseTX, 10Base2 – 1-port <sup>2</sup>
46D0020	7-34646-30314-9	MarkNet X2031e Ethernet 10/100BaseTX – 3-port <sup>2</sup>
46D0000	7-34646-30313-2	MarkNet X2030t Token-Ring – 4/16 3-port <sup>2</sup>
14T0030	7-34646-02509-6	N4000e Ethernet Print Server 10/100BaseTX – 1-port <sup>2</sup>
<b>OTHER ATTACHMENT OPTIONS</b>		
<b>Adapters</b>		
1368705	7-34646-11309-0	External Serial Adapter <sup>2</sup>
<b>Cables</b>		
1329605	0-87944-09056-4	Parallel Cable (10 ft.)
1038693	7-34646-21649-4	Serial Cable (50 ft.)
12A2405	7-34646-18340-6	USB Cable (2-meter)

<sup>1</sup> Yield is based on approximately 5% print coverage

<sup>2</sup> Connected through parallel port

<sup>3</sup> Connected through USB port



Lexmark, Lexmark with diamond design, LexExpress and MarkNet are trademarks of Lexmark International, Inc., registered in the United States and/or other countries. ENERGY STAR is a registered U.S. mark. PostScript is a registered trademark of Adobe Systems Incorporated. PCL is a registered trademark of Hewlett-Packard Company. Mac and the Mac logo are trademarks of Apple Computer, Inc., registered in the United States and/or other countries. The USB-IF logos are trademarks of Universal Serial Bus Implementers Forum, Inc. All other trademarks are the property of their respective owners. Copyright 2004 Lexmark International, Inc.