

The complete line of
Lexmark E-Series monochrome laser printers



PRINTER	Lexmark E232t, E232t	Lexmark E234n, E234tn	Lexmark E330	Lexmark E332n, E332tn
Part Number	22S0200, 22S1100	22S0602, 22S0702	22S0500	22S0600, 22S0700
Speed	Up to 22 ppm	Up to 25 ppm	Up to 27 ppm	Up to 27 ppm
Resolution	2400 Image Quality	1200 x 1200 dpi	1200 x 1200 dpi	1200 x 1200 dpi
Time to First Page	< 8.5 seconds	< 8.5 seconds	< 8 seconds	< 8 seconds
Processor	200 MHz	200 MHz	200 MHz	200 MHz
Memory (std./max.)	16MB/80MB	32MB/160MB	32MB/160MB	32MB/160MB
Paper Capacity: Standard (in/out) Maximum (in/out)	250 + 1/250 + 1 (E232) 250 + 550 + 1/250 + 1(E232t)	250 + 1/250 + 1(E234n) 250 + 550 + 1/250 + 1(E234tn)	250 + 1/250 + 1(E330) 250 + 550 + 1/150 + 1	250 + 1/250 + 1(E332) 250 + 550 + 1/250 + 1 (E332tn)
Paper Options	550 sheet drawer	550 sheet drawer	550 sheet drawer	550 Sheet drawer
Duty Cycle	Up 10,000 pages per month	Up 15,000 pages per month	Up 15,000 pages per month	Up 15,000 pages per month
Warranty	1 year limited warranty	1 year LexExpress	1 year LexExpress	1 year LexExpress

LEXMARK E Series Cartridge Offerings



Printer	Ships with 1,500 * cartridge	Ships with 2,500 * cartridge	2,500 * Replacement	6,000 * Replacement cartridge	2,500 * Return Program	6,000 * Return Program
E232	X		X		X	
E234	X		X		X	
E330	X		X		X	X
E332		X			X	X

*Yield is based on approximately 5% coverage at printer's default darkness setting.

The high performance, network laser printer designed to meet the needs of your small workgroup.

Say hello to the Lexmark E234n



- Up to 25 ppm printing
- Sturdy industrial design with a small footprint
- Compatible with multiple operating systems
- USB, Parallel and 10/100 BaseTx Ethernet network port
- Robust design supports up to 15,000 pages per month



LEXMARK™

Lexmark, Lexmark with diamond design, LexExpress and MarkNet are trademarks of Lexmark International, Inc., registered in the United States and/or other countries. Onta Forms is a trademark of Lexmark International, Inc. PostScript is a registered trademark of Adobe Systems Incorporated. ENERGY STAR is a registered U.S. mark. PCL is a registered trademark of Hewlett-Packard Company. Mac and the Mac logo are trademarks of Apple Computer, Inc., registered in the United States and/or other countries. The USB-IP logos are trademarks of Universal Serial Bus Implementers Forum, Inc. All other trademarks are the property of their respective owners.

LEXMARK™

Lexmark

E234n

The reliable desktop network laser printer for all of your personal or business applications.



E234n



E234tn

Ease of Use

- Toner low indicator, toner saver mode and job cancel button help you save time and money.
- Two-piece toner cartridge and photoconductor imaging system is clean and easy to install and replace. Why replace more than you need to?
- USB, Parallel and 10/100 BaseTx Ethernet network port standard

Reliability

- Robust design supports up to 15,000 pages per month.
- Sturdy industrial design with a small footprint for use in areas where space is limited.
- Photoconductor kit lasts up to 30,000 pages -- you may never need to replace it!

Superior Performance

- Up to 25 ppm printing
- < 8.5 seconds time to first page
- 200 MHz processor and 32MB memory
- Print complex jobs quickly

Excellent Print Quality

- Create professional, high-quality documents
- True 1200 x 1200 dpi
- Adjustable print resolution settings let you optimize print quality and performance
- Achieve high-quality results on a range of media weights and types

Lexmark E234n, E234tn

Part Number	Canada: 22S0602 (E234n), 22S0702 (E234tn)
Technology	Monochrome laser
Speed	Up to 25 ppm
Resolution	2400 image quality, 1200x1200dpi, 1200 image quality, 600x600dpi
Time to First Page	< 8.5 seconds
Processor	200 MHz
Memory (std./max.)	32MB/160MB
Connectivity	Standard: USB, Parallel and 10/100 Base Tx Ethernet network port standard Optional: MarkNet X2000 series of external print servers supported through the parallel port, N4000e Ethernet print server supported through the USB port; External serial adapter
Operating Systems	Microsoft Windows 98SE, Me, NT 4.0, 2000, XP and Server 2003; Linux; Mac OS For a complete list, visit www.lexmark.com
Emulations	PCL 6, PS3 emulation
Fonts	89 scalable fonts including OCR-A, OCR-B and Code 3 of 9 barcode. Birmapped: 2
Paper Capacity (sheets)	250 + 1/250 + 1 (E234n), 250 + 550 + 1/250 + 1 (E234tn)
Standard (in/out)	801/251 (250 + 550 + 1/250 + 1)
Maximum (in/out)	550-sheet drawer
Paper Options	
Paper Sources	2/1 (E234n) 3/1 (E234tn)
Standard (in/out)	3/1
Maximum (in/out)	Plain paper, card stock, envelopes, transparencies and paper labels
Media Types	
Media Sizes	Letter, legal, A4, A5, B5, executive, universal, statement and folio
Media Weights	Plain paper: 16-24 lb. (60-90 g/m ²) Card stock: up to 90 lb. index (163 g/m ²)
Size/Weight	E234n : 15.6" x 13.9" x 9.8" (W x D x H) (396.2 mm x 353.1 mm x 248.9 mm)/22 lb. (9.98 kg) E234tn: 15.6" x 14.8" x 14.9" (W x D x H) (396.2 mm x 376 mm x 381.9 mm)/31 lb. (14.0 kg)
Acoustics	52 dBA printing; 30 dBA idle
Supplies ¹	Ships with: 1,500-page Starter Return Program Toner Cartridge and up to 30,000-page Photoconductor Kit Supplies: 2,500-page Return Program Toner Cartridge 2,500-page Toner Cartridge 30,000-page Photoconductor Kit
Duty Cycle	Up to 15,000 pages per month
Warranty	1-year LexExpress

Additional Options

Description	Part No.	UPC
Print Cartridges		
12A8400	7-34646-38629-6	2,500-page Return Program Toner Cartridge
12A8300	7-34646-38626-5	2,500-page Toner Cartridge
Other Supplies		
12A8302	7-34646-38627-2	Photoconductor Kit
Media		
70X7240	7-34646-03810-2	Transparencies (Letter, 50 sheets)
Paper Handling Options		
22S0302	7-34646-02417-4	550-Sheet Drawer with Tray
Memory Options		
16H0056	7-34646-24756-6	16MB SDRAM
16H0057	7-34646-24757-3	32MB SDRAM
16H0058	7-34646-24758-0	64MB SDRAM
16H0059	7-34646-24759-7	128MB SDRAM
Part No.	UPC	
Adapters		
1368705	7-34646-11309-0	External Serial Adapter
1010043	7-34646-11802-6	802.11g Wireless Print Adapter
Cables		
1329605	0-87944-09056-4	Parallel Cable (10 ft.)
1038693	7-34646-21649-4	Serial Cable (50 ft.)
12A2405	7-34646-18340-6	USB Cable (2-meter)

¹Yield is based on approximately 5% coverage at printer's default darkness setting.